



14 Series 1440 H



Acqua fredda
Cold water



Per uso frequente
For frequent usage



Accessori professionali
Professional accessories

POWERED by
HONDA

Caratteristiche Generali - General Features:

- Carrello completo di manico con due ruote con battistrada in gomma e piedini antivibranti
- Pompa a 3 pistoni assiali comandati dal piattello oscillante
- Testa pompa in ottone
- Valvola di by-pass automatica
- Regolazione della pressione (mod. 1440H)
- Valvola termica
- Aspirazione detergente
- Motorizzato Honda
- Livelli olio ispezionabili
- Tappi ed asole di scarico per agevolare la manutenzione ed il cambio olio
- Filtro acqua ispezionabile
- Two-wheel trolley with rubber tread wheels, handle and damper feet inflatable pneumatic wheels and anti-vibrating feet
- 3 Axial stainless steel pistons wobble-plate pump
- Brass pump head
- Automatic by-pass valve
- Pressure adjustment (mod. 1440H)
- Thermal valve
- Detergent suction
- Powered by Honda
- Inspectable oil levels
- Discharge plugs and discharge slots to make easy the maintenance and the oil change
- Inspectable water filter



ø 28 cm

Fornito con - Equipped with:

AL 13
Pistola 3/8" (M) M22x1,5
Trigger gun
(41045)



Lancia
Lance
(3600650)



Ugello/Wash nozzle 1430 H
Bassa pressione / low pressure (3600400) - Nero / Black
Getto dritto / pencil jet SS 00025 (3600890) - Rosso / Red
Getto ventaglio / fan jet SS 15025 (3600900) - Giallo / Yellow
Getto ventaglio / fan jet SS 40025 (3600920) - Bianco / White

Tubo armato AP 8 m
HP reinforced hose 8m
tipo / type DN8, PN 250 bar (50689)



Ugello/Wash nozzle 1440 H
Bassa pressione / low pressure (3600400) - Nero / Black
Getto dritto / pencil jet SS 0003 (3600440) - Rosso / Red
Getto ventaglio / fan jet SS 1503 (3600450) - Giallo / Yellow
Getto ventaglio / fan jet SS 4003 (3600470) - Bianco / White



Ruote con battistrada in gomma
Piedini antivibranti
Rubber tread wheels
Damper feet



Gancio porta accessori
Accessories holder



Serbatoio detergente integrato

Built-in detergent tank



1440 H
(RMV)
GC 160

Dati Tecnici / Technical Data

MOD	COD	MAX		l/h	gph	HP	rpm	kg
		bar	psi					
1440 H	25676	200	2900	550	145	4,6	3400	39

Temperatura massima acqua / Max inlet water temperature 50°C 122°F IPX5-S1